



## Roli™ Cradle - For pipe sizes 6" [168mm] to 60" [1524mm]

**The CRC-Evans Roli™ Cradle is the ideal cradle to provide lift and support for all line-travel operations.**

It features non-marring rollers with anti-friction bearings mounted on high-strength cables.

- Pipe damage caused by steel wheel cradles is eliminated
- Pressure on the pipe is distributed evenly over multiple urethane rollers, eliminating 'egging' of the pipe
- Urethane rollers ride easily over weld seams and do not hang up
- Easily disassembled for storage and transit
- Ample capacity ensures safe handling of heavy wall pipe
- Also suitable for use as a lowering-in or lift-out cradle
- Wraparound design ensures that the pipe 'centers' in the cradle
- Available in five ranges to accommodate pipe sizes 6" (168mm) through 60" (1524mm)

## Specifications

Model No.	Part No.	Size		Number of rollers per string	Recommended max working load 5:1 safety factor (with two strings)		Length*		Width*		Height*		Weight*	
		inch	mm		lb	kg	inch	mm	inch	mm	inch	mm	lb	kg
RC 6-12	D30528	6-12	168-324	10	16293	7676	42	1067	22	559	30	762	1135	515
RC 12-24	D30529	12-24	305-610	14	28622	13001	42	1067	36	914	36	914	1500	680
RC 24-36	D30530	24-36	610-914	12	56500	25628	56	1422	60	1524	36	914	4960	2250
RC 36-48	D30531	36-48	914-1219	16	69389	31474	56	1422	72	1828	42	1067	6425	2914
RC 48-60	D30532	48-60	1219-1524	18	105380	47800	56	1422	84	2134	48	1219	7240	3284

\* Denotes dimensions collapsed for shipping purposes.

**Note:** Each cradle has two (2) strings.

**Capacity:** The capacities given in the table above are calculated with a safety factor of 5:1. Recalculate these capacities if your local laws or regulations allow a different safety factor.

Roli™ Cradles may be used with any size of side boom, but care must be taken not to exceed the recommended maximum working load of the Roli™ Cradles.



### ! Disclaimer

Although great care has been taken in compiling the information contained in this catalogue, CRC-Evans does not accept responsibility for the consequences of any errors, nor for the effects of any subsequent changes made by the various sources of data.

Dimensions and weights provided for reference only. Dimensions, specifications and weights can vary depending upon final configuration of the equipment. Please contact CRC-Evans to confirm final weights and dimensions prior to shipment.



Houston: (832) 249-3100 Toll Free: (800) 664-9224 • Tulsa: (918) 438-2100  
Netherlands: +31-36-711-7500 • [www.crc-evans.com](http://www.crc-evans.com)